




閥調式鉛酸蓄電池(VRLA)
Valve Regulated Lead Acid Battery

UXH50-12I

尺寸 DIMENSION



規範 Specification

- 公稱電壓 Nominal Voltage : 12V
- 操作溫度範圍 Operating Temperature Range
 - 放電 Discharging -15°C to 45°C
 - 充電 Charging -15°C to 45°C
 - 放置 Storage -15°C to 45°C
- 尺寸 Dimension
 - 長度 Length : 197±2mm
 - 寬度 Width : 165±2mm
 - 高度 Case Height : 175±2mm
 - 總高 Overall Height : 175±2mm
- 期待浮充壽命 Expected float use life (25°C) : 10 years
- 重量 Weight (約 Approx.) : 15.7 kg
- 容易保養 Easy Maintenance
 - 不會洩漏電解液 No electrolyte leakage
 - 確保操作上安全性 Ensure safe and efficient operation
- 公稱容量 Nominal Capacity : 50AH / 20HR (25°C)
- 電槽材質 Container Material :
 - 難燃ABS Flame Retardant ABS · 難燃等級Flame class : UL94V0
 - 氧氣指數 Oxygen index : 28.0% LOI
- 內部抵抗 Internal Resistance(Approx.) : 約 5.7 mΩ
- 最大充電電流 Max. Charge current : 12.5A
- 最大連續放電電流
 - Max. Continuous discharge current : 150A
- 用途 Applications :
 - UPS 不斷電系統、電信、緊急照明、警報系統、儀器、太陽能發電系統
 - UPS(Uninterruptible Power Supply) · Telecommunications · Emergency lighting · Alarm systems · Instrumentation · Solar powered systems
- 5 秒最大放電電流
 - Max. Discharge current in 5 seconds : 400A
- 浮動充電 Float Charging : 13.65±0.15V (25°C)
- 端子 Terminal :
 - 極柱端子Top terminal : 螺絲式 Bolt (M5)


UXH50-12I 性能規格 PERFORMANCE SPECIFICATION : 安培 Amperes and 瓦特 Watts at 25 °C (77 °F)

F.V.	TIME	5M	10M	15M	20M	30M	45M	1H	2H	3H	4H	5H	10H	20H
		10.80V	W	1588	1166	927	763	573	423	337	194.1	137.6	110.1	93.5
	A	144	101	80	65	49.1	36.1	28.7	16.29	11.47	9.17	7.80	4.14	2.49
10.50V	W	1699	1222	958	785	587	432	344	196.4	138.8	111.0	94.3	50.2	27.4
	A	154	108	83	68	50.6	37.0	29.2	16.51	11.59	9.27	7.88	4.18	2.50
10.20V	W	1811	1270	980	800	596	437	346	197.6	139.6	111.6	94.9	50.5	27.5
	A	167	114	85	69	51.4	37.4	29.4	16.57	11.62	9.29	7.90	4.19	2.51
10.02V	W	1846	1288	987	804	598	438	346	197.8	139.7	111.7	95.0	50.6	27.6
	A	171	115	85.8	69.5	51.6	37.5	29.5	16.59	11.63	9.30	7.91	4.20	2.51
9.60V	W	1943	1340	1008	818	606	441	347	198.4	140.1	112.1	95.2	50.7	27.7
	A	183	121	88	71	52.5	37.9	29.6	16.65	11.67	9.34	7.94	4.21	2.52


特性 Characteristics

放電特性 DISCHARGE CHARACTERISTICS


放電曲線 Discharge Characteristics Curves at 25°C




浮充期待壽命 Float Service Life



充電特性 CHARGE CHARACTERISTICS



充電電壓 CHARGE VOLTAGE



臺灣湯淺電池股份有限公司 新北市新莊區福營路 227 巷 11 號 TEL:(02)2901-8261 FAX:(02)2903-9626
 TAIWAN YUASA BATTERY CO.,LTD No.11, Ln. 227, Fuying Rd., Xinzhuang Dist., New Taipei City <http://www.yuasa.com.tw/>